


Curve 5D in acciaio al carbonio



R=5D
CURVE SENZA SALDATURA
EN 10253-2

R=5D
SEAMLESS ELBOWS
EN 10253-2

CARBON STEEL

| Ø EST.MM OUTS.DIAM MM | Spessore Thickness | Raggio Radius | H | Peso Teorico Theoretical Weight Kg |
|--------------------------|-----------------------|------------------|------|--|
| 48,30 | 2,60 | 190 | 214 | 0,87 |
| | 3,60 | | | 1,18 |
| 60,30 | 2,90 | 254 | 284 | 1,64 |
| | 4,00 | | | 2,22 |
| 88,90 | 3,20 | 381 | 425 | 4,05 |
| | 5,60 | | | 6,88 |
| 114,30 | 3,60 | 508 | 585 | 7,84 |
| | 6,30 | | | 13,39 |
| 168,30 | 4,50 | 762 | 846 | 21,76 |
| | 7,10 | | | 33,78 |
| 219,10 | 6,30 | 1016 | 1126 | 52,76 |
| | 8,00 | | | 66,47 |
| 273,00 | 6,30 | 1270 | 1407 | 82,66 |
| | 8,80 | | | 114,38 |
| 323,90 | 6,30 | 1524 | 1666 | 118,13 |
| | 8,80 | | | 163,70 |
| | 10,00 | | | 185,32 |
| 355,60 | 7,92 | 1956 | 2136 | 208,65 |
| | 9,50 | | | 249,13 |
| 406,40 | 7,92 | 2235 | 2438 | 273,24 |
| | 9,50 | | | 326,45 |